Well-Mix SP



High Range Water Reducing Cum Retarding Admixture

Description

Well-Mix SP is a high range water-reducing admixture formulated specifically to extend the working time of concrete. It is based on Naphthalene Formaldehyde.

Well-Mix SP conforms to specification prescribed in IS 9103 & ASTM C 494, Type G

Characteristics

| Colour | Amber brown | Specific Gravity | 1.20 ± 0.03 |
|--------|-------------|------------------|-----------------|
| Ph | 7 – 8 | Chloride Content | Nil |

Application

- High performance concrete.
- Ready mix concrete.
- Flowing concrete.
- Heavily reinforced concrete.
- Pump-able concrete.

Advantages

- Produces Flowing concrete with controlled delay of slumps loss and workability.
- Reduces cracking and permeability of hardened concrete.
- Reduces segregation and bleeding in the plastic concrete.
- Significantly reduces concrete placement time and cost.
- Long time workability retention.
- Enable transport of concrete to distant places

Application Methodology

- Add Well-Mix SP to the dosing water. It should not come into contact with dry cement.
- Charge all concrete material in the proper order into the mixer with about 70 % of the mixing water and mix for the three minutes. Add the rest quantity of water with admixture to obtain the required slump and mix for three additional minutes.
- Forms for walls or narrow sections must be watertight, strong and must have good bracing.
- During the "Flowing period" the concrete will exert a higher pressure at the base of the form than conventional concrete. Formwork for slabs is the same as for conventional concrete.
- Compatible with all types of Portland cement including SRC (Sulphate Resistance Cement) and not compatible with high alumina cement.

Dosage

0.8 - 2 % by weight of cement. Do not allow over dosing. Due to overdosing setting time will be extended rigorously. It is advisable to carry out a trial to establish the exact & optimal dosage rate depending upon set retardation required.

Health & Safety

- Well-Mix SP is non-toxic.
- Any splashes on the skin should be washed immediately with water.
- Splashes on the eyes should be washed immediately with water and seek medica

Packing

Available in 250 Kg drums.

Storage

Store in a cool dry place under a shed away from heat.

Shelf Life : 12 months in original sealed condition.

Well Knit's Businesses

Protective / Anti-Corrosive Coating Product Admixtures / Grouts / Sealants & Additives Other Chemical Product



Mo.+91 97562 07683, 70377 95299

Plot No.64, Shri Krishna Industrial Estate Moja nougaon

Sonkh Road Mathura (UP) 202001

Email: Wellknit_chem@outlook.com

Website: www.wellknitchemical.com